



ASC4035050 Kindling
Brick Installation



ASC4005050 Zero Gravity
Quarter-Turn Installation

Ascension

FIBER SYSTEM

Solution Dyed Nylon

SIZE

19.7" x 19.7" (nominal) 50 cm x 50 cm

PILE WEIGHT

18 oz/SY 610 g/m²

GAUGE

1/12

DENSITY

5500

PACKAGING

20 tiles per carton = 6 SY = 5 m²

BACKING SYSTEM

Enhanced Core Modified Bitumen

TESTING

Flammability Class I (ASTM E648)
 Bfl-s1 (EN13051-1)
Static <2 kV (AATCC 134)
Usage Classification 33 (EN1307)

LIFETIME COMMERCIAL WARRANTIES

- Stain Resistance
- Backing Performance
- Commercial Wear


See website for full warranty details.

SUSTAINABILITY

- CRI Green Label Plus
- 100% PVC-Free
- Up to 20% pre-consumer recycled content

INSTALLATION METHODS

- Ashlar
- Brick
- Monolithic
- Quarter-Turn



ASC4005050
Zero Gravity



ASC4015050
Hematite




ASC4025050
Coastal Storm



ASC4035050
Kindling



ASC4045050
Canyon



ASC4055050
Downpour