



CASCADe
LUXURY VINYL

IMPACT
LUXURY VINYL TILE



IMP02 Electric Grey




IMP03 Ocean Sand



IMP04 Park Ave Slate



IMP09 Rodeo Mist




IMP10 Sunset Khaki



IMP12 Wall St Steel




IMP66 Cathedral Brown



IMP14 Hyde Park Brown



IMP17 Camben St Tan



IMP56 Roasted Truffle




IMP26 Bedrock



IMP27 Arctic Express



IMP20 Canal St Fawn




IMP22 Victoria Grey




IMP71 Ashford Marble




IMP28 Frosted Grey



IMP50 Duke St Wash



IMP55 Iron Wood



IMP65 Horse Shoe Beige




IMP73 Carbon Concrete



IMP85 Sandalwood




IMP67 Wolf Grey




IMP69 Lighthouse Oak



IMP72 Harbour Stone




IMP84 Apple Wood




IMP74 Urban Slab



IMP80 Cabana Natural



IMP81 Earl Grey



IMP83 Light Latte



IMPACT SPECIFICATIONS

Constructions	PVC
Thickness	2mm
Wear Layer	0.3mm 12 mil
Size	7" x 48" / 12.36" x 24.6"
Finish	Polyurethane w/ anti bacterial nano silver, satin gloss
Edge Detail	Square edge
Sf Per Carton	12.36" x 24.6" = 52.81" 7" x 48" = 51.33
Sf Per Pallet	12.36" x 24.6" = 24.6" = 2,746.12 7" x 48" = 3,079.80
Installation	Glue Down
Classification	Good
Residential Warranty	25 Year Limited Residential
Commercial Warranty	10 Year Limited Medium Commercial
Recommended Adhesive	Cascade XT360
Approved Adhesives	Wolf Grip Premium, Armstrong S - 995.
Emissions	FloorScore Certified

PERFORMANCE TESTING

Fire Rating	ASTM E84 75 or less
Mekel Burner Test	Pass
Heat Stability	KSM 3802 0.3mm/ 0.01"80C+2C, 6hr/1hr
Abrasion Resistance	ASTM D3884 0.1% Loss
Slip Resistance ADA	Exceeds ADA Requirements
Dry Static Coefficient Of Friction	ASTM C1028 0.72
Wet Static Coefficient Of Friction	ASTM C1028 0.67
Residual Indentation	EN 433 ≤ 0.10mm
Color Fastness	ISO 105-B02 ≥ 6
Dimensional Stability	EN 434 ≤ 0.10mm
Flexibility	EN 435 No crack was found
Electrical Behavior	EN 1081 Pass

IMPACT
LUXURY VINYL TILE

